

POLYKEN®

44SA

Low VOC Premium Web Spray Adhesive



Product Size:	14 oz Net Wt; 19.6 FL OZ
Spray Pattern:	Lace
Color:	Water White
% Solids:	24% Premium Resins
Operating Temp:	-10 to 180 °F (-23 to 82 °C)
Bonding Time:	1 minute to one hour
Evaporation Time:	20-30 seconds
Coverage Area:	Varies
Shelf Life:	1 Year from DOM
VOC Content:	<40% by weight

Meets FDA requirements for indirect food packaging when used according to 21 CFR 175.105.

Applications

- Carpet bonding
- Bonding fabric, insulation, plastic films, felt, wood, rubber, leather, cork, paper,
- Attaching insulation materials to duct work
- Laminating foam materials
- Securing labels
- Surface priming
- Suitable for permanent or temporary bonds

Features

- Rubber Based
- Low VOC Content

Benefits

- Fast skin, fast grab, low soak-in
- Performs over a wide temperature range
- Good UV, moisture, and oxidation resistance
- Meets SCAQMD Rule 1168 and GreenSeal GS-36 requirements
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Application Instructions

- Shake well before applying. Spray an even coat from a distance of 6-8 inches.
- For permanent bonds, spray both surfaces. Allow 1-2 minutes for tack to develop. Apply firm pressure
- For temporary bonds, apply a light, even coat to one surface; allow tack to develop. Apply firm pressure.
- When finished spraying, turn can upside down and spray for 2 seconds to prevent nozzle from clogging.

Caution: Extremely Flammable. Please review all safety instructions on the product package prior to use.

Recommended Storage Conditions: 60-80 °F at 40-60% RH
Standard Shelf Life (at 25 °C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038
1-800-343-7875 Fax 1-800-328-4822
www.berryglobal.com
6/24/19