


## Heavy Duty Foil/Butyl Tape



- Backing:** 2 mil Aluminum Foil - Printed
- Adhesive:** Butyl Rubber
- Liner:** Blue LDPE
- Colors:** Aluminum
- Specifications:** UL 723 Classified and tested in accordance with CAN/ULC-S102-10
- Standard Sizes:** 48mm x 31m, 72mm x 31m

### Applications

- Duct joint sealing for low, medium, and high pressure HVAC systems
- Repairs in aluminum siding, sheet metal, gutters, storage buildings, flashing, containers, and more

### Features

- Aggressive butyl mastic adhesive
- Conformable foil backing
- Low VOC Content

### Benefits

- Provides instant water and air-tight seal
- Resistant to moisture and solvents
- Permanent repairs
- Easy to use in tight spaces. Conforms easily to round, square or odd-shaped objects
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	17.0 mils	0.432 mm	ASTM D-1000
<b>Foil Thickness</b>	2.0 mils	0.051 mm	ASTM D-1000
<b>Adhesion to Steel</b>	200 oz/in	21.88 N/cm	PSTC-101
<b>Tensile Strength</b>	20 lb/in	35.03 N/cm	ASTM D-1000
<b>Flame Spread</b>	5		UL 723 & CAN/ULC-S102-10
<b>Smoke Developed</b>	10		UL 723 & CAN/ULC-S102-10
<b>Operating Temperature</b>	40 to 200 °F	4 to 93 °C	
<b>VOC Content</b>	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH  
 Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.