



Engineered Tapes for HVAC

The **Polyken**® brand is highly recognized within the HVAC industry as the premium source for exceptional duct sealing tapes that provide long-term reliability. **Polyken**® tapes have been used in a wide range of heating, ventilating, and air conditioning applications to ensure energy efficiency in residential and commercial buildings for more than 50 years.

Polyken® products are designed to meet rigorous customer and industry performance requirements while providing long-term durability. All **Polyken**® adhesive systems for HVAC applications are made with low VOC (volatile organic compound) formulations to protect the homeowner and the contractor.



MADE IN U.S.A. OF U.S. & GLOBAL COMPONENTS
Hecho en EE.UU. con componentes globales y de E.E.U.U.



1.800.343.7875 | berryglobal.com

Polyken®, FlexFix®, and FoilMastic™ are trademarks of Berry Global, Inc. or one of its affiliates.

5377



Sheet Metal



Duct Board



Flexible Duct



POLYKEN®

POLYKEN[®] HVAC Tapes

Outstanding cold weather performance. Instant adhesion and superior quick stick. Mold resistant.

Colors: Aluminum (Printed)
 Sizes: 2.5 in x 60 yd,
 72 mm x 55 m

Thick 1.75 mil aluminum foil facer. High tack, high adhesion rubber adhesive. UL 723 Classified.

Colors: Aluminum
 Sizes: 48 mm x 46 m,
 72 mm x 46 m

Performs in extreme cold conditions. Aggressive quick stick. Mold resistant. UL 723 Classified.

Colors: Aluminum
 Sizes: 48 mm x 46 m,
 72 mm x 46 m

High adhesion and tensile strength. Crisp, straight tear.

Colors: Metallic, Black, Silver
 Sizes: 48 mm x 55 m,
 72 mm x 55 m

Contractor tough film is durable and hand-tearable. High tack adhesive bonds quickly and holds strong.

Colors: Metallic, Black
 Sizes: 48 mm x 110 m,
 72 mm x 110 m

Excellent balance of tearability and tensile strength. Aggressive adhesion on rough surfaces.

Colors: Metallic
 Sizes: 48 mm x 55 m,
 72 mm x 55 m

339

UL 181A-P & UL 181B-FX Listed

Premium cold weather foil tape for rigid fiberglass duct board and Class 1 flexible duct.

337

Multi-Purpose Grade

Sealing duct work for HVAC-R systems. Insulation patching and seaming.

330X

Extreme Weather

Extreme cold temperature duct and insulation seaming applications.

557

UL 181B-FX Listed

Premium PE-coated cloth tape for sealing Class 1 flexible duct.

555 FlexFix[®]

UL 181B-FX Listed

Seals Class 1 Flexible Duct and Connectors. Superior adhesion to foam pipe and bubblewrap insulation.

251

11 mil Pro Grade—Metallic

Duct and joint sealing where a metal finish is desired.

Synthetic rubber adhesive offers excellent tack and adhesion. Tough, tear resistant facer.

Colors: Aluminum
 Sizes: 48 mm x 46 m,
 72 mm x 46 m

Extreme weather acrylic adhesive withstands high heat and humidity and bonds even in extreme cold. Tough and durable. Mold resistant.

Colors: Aluminum
 Sizes: 72 mm x 46 m

Super tough embossed foil laminate backing resists puncture. Mold and moisture-resistant adhesive bonds permanently and withstands cold temperatures.

Colors: White, Metallic
 Sizes: 4 in x 15 yd

Good balance of adhesion, tack and tensile. Excellent tear. Clean removal from most surfaces. Tested in accordance with UL 723.

Colors: (223) Silver, Black, Red, White, Blue, Green, OD, Yellow; (243) Silver, Black
 Sizes: 48 mm x 55 m,
 72 mm x 55 m

High adhesion for difficult surfaces. Crisp, straight tear. Tested in accordance with UL 723.

Colors: Silver, Black, Red, White, Blue, Green, OD, Yellow
 Sizes: 48 mm x 55 m,
 72 mm x 55 m

Excellent balance of adhesion, tensile, and tack. Excellent tear. Highly conformable. Tested in accordance with UL 723.

Colors: Silver, Black
 Sizes: 48 mm x 55 m,
 72 mm x 55 m

338

FSK Jacketing Tape

Foil/Scrim/Kraft tape for insulation sealing and patching.

438

Extreme Weather Jacketing Tape

Foil/Scrim/Kraft tape for insulation sealing and patching.

334CRT

Cooler Repair Tape

Seals seams, cracks, and corners against air leakage for walk-in refrigeration units, refrigerated trailers, etc.

223/243

10 mil Multi-Purpose Grade

Bundling, packaging, seaming, general repairs, and color coding.

227

11 mil Professional Grade

Long-term heavy duty sealing and seaming. Color coding.

229

12 mil Professional Grade

Premium waterproof duct tape for seaming, repairing, and patching HVAC systems.

Permanent air-tight and waterproof bond but can be repositioned during installation. Conformable, durable, and puncture resistant. Performs up to 10" w.g. pressure.

Colors: Aluminum (Printed)
 Sizes: 48 mm x 31 m,
 72 mm x 31 m

Forms instant, permanent water-tight bond. Excellent temperature and moisture resistance. UL 723 Classified.

Colors: Aluminum (Printed)
 Sizes: 48 mm x 31 m,
 72 mm x 31 m

Excellent extreme temperature resistance up to 500F°. Resistant to UV, mold, and moisture. Low odor, low VOC. Tested in accordance with UL 723.

Colors: Aluminum
 Sizes: 48 mm x 46 m,
 72 mm x 46 m

High adhesion and tensile strength. Puncture and abrasion resistant.

Colors: Silver (Printed and Unprinted), Black, Red, White
 Sizes: 48 mm x 55 m,
 72 mm x 55 m

Matte-finish cloth tape with rubber based adhesive. Holds strong yet removes cleanly from surfaces.

Colors: Black
 Sizes: 48 mm x 50 m

UV Resistant. Acrylic adhesive offers excellent adhesion to foam and all-weather performance. Resists lifting and flagging.

Colors: Black (Printed and Unprinted)
 Sizes: 48 mm x 55 m

367-17 FoilMastic[®]

UL 181B-FX Listed

Premium foil/butyl tape for flexible and rigid sheet metal ducts.



360-17

FoilMastic[®] Tape

Indoor/outdoor sealing of sheet metal ducts, gutters, trailers, and more.

335FT

High Temperature Flue Tape

Seals closures in high heat flue installations and for use on high efficiency furnace-certified plastic vent pipes.

253

13 mil Premium Grade

Industry-standard waterproof premium duct tape for sealing and general repairs.

510

Gaffer Tape

Indoor wire hold down, bundling, and repairs

444

Lineset Tape

Wrapping and protecting outdoor line sets for heating, cooling, and ventilation systems.